

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B65B 55/06	A1	(11) International Publication Number: WO 98/16431 (43) International Publication Date: 23 April 1998 (23.04.98)
(21) International Application Number: PCT/SE97/01574 (22) International Filing Date: 18 September 1997 (18.09.97) (30) Priority Data: 9603782-5 16 October 1996 (16.10.96) SE (71) Applicant (for all designated States except US): TETRA LAVAL HOLDINGS & FINANCE S.A. [CH/CH]; Avenue Général-Guisan 70, CH-1009 Pully (CH). (72) Inventor; and (75) Inventor/Applicant (for US only): LAGERSTEDT, Jan [SE/SE]; Fyrspanngatan 16, S-216 21 Malmö (SE). (74) Agents: PETRI, Stellan et al.; Ström & Gulliksson AB, P.O. Box 4188, S-203 13 Malmö (SE).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the</i> <i>claims and to be republished in the event of the receipt of</i> <i>amendments.</i> <i>In English translation (filed in Swedish).</i>
(54) Title: A METHOD OF STERILIZING CONTAINERS BASED ON FIBER (57) Abstract When autoclaving a fibre-based container the cycle time of the sterilizing process can be reduced by the heat transfer medium used for heating and/or the cooling, respectively, of the container being exchanged at a critical temperature for the container.		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Licchtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

A METHOD OF STERILIZING CONTAINERS BASED ON FIBER

The present invention relates to a method of sterilizing fibre-based containers. More specifically, the invention relates to a method in connection with autoclaving a fibre-based container, the cycle time of the sterilizing process being reduced.

A heat treatment for killing and/or inactivation of microorganisms can be accomplished by means of moist as well as dry heat. In the food industry the heat treatment in moist heat is preferred since the biological killing and inactivating mechanisms are much more effective at a high water content than at a low water content, i.e. dry heat. Besides, the heat transfer in the equipment used for the heat treatment is much more effective with moist heat.

In a package material having a base layer of paper or board this layer must be made relatively thick in order to give the container a necessary dimensional rigidity. However, containers made of these laminates based on paper or board have the drawback of rapidly losing their mechanical strength properties when they are subjected to liquid or moisture, which results in that the container becomes flabby and cumbersome. Thus, such known containers made of a packaging laminate with a liquid absorbing fibre layer cannot be subjected to a heat treatment with moist heat without the desired mechanical rigidity of the packaging laminate and thus the dimensional stability of the container being impaired or lost.

In order to avoid these problems packaging laminates have been developed which are adapted to withstand drastic conditions in the form of moisture and/or heat. Such a known alternative package material has for example a strengthening base layer of plastic and a filler intermixed with the plastic. This material has proved to be less moisture sensitive than the previously used materials based

on paper and board. Containers manufactured from these laminates are very suitable for preservation by means of refrigeration as well as heat. When a preservation by means of refrigeration is used these containers with a solid
5 and/or liquid filling material can be chilled by means of water cooling.

However, paper and board are cheap package materials, and containers have thus been developed which comprise a laminate with a base layer of one of these materials.
10 Containers manufactured from such a material of laminate type in the form of a sheet or a web can be heat treated in a humid atmosphere at high temperatures.

These laminates can by means of folding be used for the manufacture of dimensional stable impermeable packaging
15 containers which are very suitable to be used at most extreme conditions in a humid environment including heat treatment with moist heat at an overpressure. Such harsh environments comprise autoclaving at temperatures and periods which are accepted for foods. This means that the
20 laminate is also highly suitable to be used for the manufacture of a container which is intended to be filled with a product under aseptic conditions. In this connection the product is sterilized and filled under almost sterile conditions in a likewise sterilized container which after
25 filling is sealed in such a way that the filled product during storage is not reinfected by microorganisms before it is consumed.

Such a heat treatment of the containers is achieved with a heat transfer medium containing water. Generally, a
30 heat treatment with moist heat is utilized at overpressures in autoclaves which are filled with water or steam. In this connection an autoclaving cycle can be divided into a rise time, a holding time, and a cooling time. The rise time is the time from the beginning of the heating and until the
35 desired temperature has been reached. At an overpressure of

0.5 bar the steam has a temperature of about 110 °C, and at an overpressure of 1.1 bar the temperature becomes about 121 °C. After the holding time, which is the time required to achieve a sterilization at the desired constant temperature, the pressure in the autoclave is lowered to a normal atmospheric pressure, and during the cooling time the temperature is lowered by means of cooling the autoclave.

Since autoclaving is a sterilization method which uses an overpressure this method is mostly performed as a batch procedure and not continuously. It is thus of interest to be able to reduce the cycle time when autoclaving.

However, it has become apparent that when the above-mentioned containers are too extensively heat treated they are subjected to environments whereby the good sealing properties of the containers against moisture and liquid partly are lost. Due to the soaking paper or board layers it is in this way a risk that the package material loses its mechanical strength properties and that the container becomes flabby and cumbersome. It is thus important that this type of containers is exposed to such environments to the smallest extent possible.

In order to solve the problems mentioned above the method according to the invention has been given the characterizing features of claim 1.

When sterilizing containers containing fibre the cooling of the containers has previously been effected with air in order to compensate for the problems mentioned above. However, it has been shown in connection with autoclaving that such containers with for example a soaking layer of paper or board very well tolerate heating up to a critical temperature as well as cooling with water in liquid phase as a heat transfer medium.

Different types of material require different process times and/or different times for heating/killing/cooling. Above all, the critical temperature depends on the thick-

ness of the base layer and of the fibre content in its composition, but the other components of the packaging laminate are also of importance. Thus, the critical temperature varies between about 70 °C and about 95 °C, preferably between about 80 °C and about 85 °C. With a folded container manufactured from a material of the laminate type in the form of a sheet or a web, which material comprises a base layer, an outer coating and an inner coating, the critical temperature can be as high as about 90 °C.

The sterilization of filled containers by means of autoclaving is carried out in a cyclic course. Such a cycle comprises the above mentioned phases following each other: rise time, holding time, and cooling time. The heat transfer medium can according to the invention be exchanged during the rise time and/or during the holding time. Since for example cooling with air is considerably slower than cooling with water a combined cooling procedure for containers which are based on fibre and which can be autoclaved, in which procedure the air is replaced with water-cooling, results in that a shorter cooling time is achieved. In the corresponding way a heating with steam is faster than to spray with water, which is a usual pre-heating method in connection with heat treating processes. Thus, such exchanges of the heat transfer medium improve the efficiency of the sterilizing cycle, and this in turn results in an improved process economy.

In this connection a heat transfer medium means an agent which transfers heat energy from or to the container. Suitable heat transfer media comprise for example water (in liquid phase), steam, and air. During the cooling of a container after the sterilization by means of for example autoclaving the heat transfer medium is according to the invention exchanged at the critical temperature, preferably from air to water. The cooling below the critical temper-

ature can also be accomplished by means of spraying with cool water, if necessary with an accompanying cooling with CO₂ or N₂ in order to rapidly achieve a sufficiently low temperature. With this in view it is also possible to end
5 the cooling phase with dry blowing. In the same way the heat transfer medium can be exchanged at the critical temperature during the heating of a container before autoclaving.

In summary, package materials exist which are exposed
10 to environments requiring good sealing properties of the container against moisture and liquid. Above a certain critical temperature these materials can not completely withstand the negative effect of the water on the mechanical properties of the package material. Consequently,
15 the containers are exposed to these non-favourable conditions as briefly as possible while maintaining the sterilization effect required. This is according to the invention achieved by the heat transfer medium used for heating and/or cooling of the container, respectively,
20 being exchanged during the heating and/or cooling of the container at a critical temperature for the container when it is sterilized by means of heat treatment, preferably autoclaving. Preferably, the sterilization is performed in an autoclave, the temperature of which is allowed to rise
25 to the autoclaving temperature suitable for the application, which temperature is maintained during a sufficient holding time. Then the container is cooled with a medium not containing water, which medium preferably is air, down to the critical temperature, at which temperature the
30 medium is exchanged for water.

Calculations from experiments in practice have shown that the process time can be reduced considerably by means of this cycle of steam-air-water. In dependence of the type of container the cooling time can for example be shortened

with about 10 minutes from earlier duration times of about 30-50 min.

CLAIMS

1. Method in connection with autoclaving a fibre-based container, characterized in that
5 during the heating and/or cooling at a temperature critical for the container, the heat transfer medium used for the heating and/or the cooling, respectively, of the container is exchanged.

2. Method as claimed in claim 1, characterized
10 terized in that the medium during the cooling is exchanged from air to water.

3. Method as claimed in claim 1, characterized in that the critical temperature is between about 70 °C and about 95 °C.

15 4. Method as claimed in claim 3, characterized in that the critical temperature is between about 80 °C and about 85 °C.

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 97/01574

A. CLASSIFICATION OF SUBJECT MATTER		
IPC6: B65B 55/06 According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED		
Minimum documentation searched (classification system followed by classification symbols)		
IPC6: B65B, A61L		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
SE,DK,FI,NO classes as above		
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 4296067 A (NÄSMAN ET AL), 20 October 1981 (20.10.81)	
	--	
A	US 4497773 A (KUELZOW ET AL), 5 February 1985 (05.02.85)	
	--	

<input type="checkbox"/> Further documents are listed in the continuation of Box C. <input checked="" type="checkbox"/> See patent family annex.		
* Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "&" document member of the same patent family		
Date of the actual completion of the international search		Date of mailing of the international search report
23 January 1998		09.02.98
Name and mailing address of the ISA/ Swedish Patent Office Box 5055, S-102 42 STOCKHOLM Facsimile No. +46 8 666 02 86		Authorized officer Kristina Pederson Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT
Information on patent family members

07/01/98

International application No.
PCT/SE 97/01574

Patent document cited in search report			Publication date	Patent family member(s)	Publication date
US	4296067	A	20/10/81	DE 3003305 A	07/08/80
				DK 40380 A	31/07/80
				DK 146405 B,C	03/10/83
				FR 2447722 A,B	29/08/80
				GB 2042895 A,B	01/10/80
				NL 8000597 A	01/08/80
				SE 412990 B	31/03/80

US	4497773	A	05/02/85	NONE	
